



"Mini" Stereo Microphones

DSLR – Mini DV

SMX-20 **Stereo Microphone**

Directional High Performance Microphone

- Reduces Side and Background Sounds
- Small Size (<5") – Big Sound (Wide Response)
- Shock-mount Microphone Holder with Shoe
- Removable Foam Windscreen



SMX-10

SMX-5



Specifications*

	SMX-20	SMX-10	SMX-5
Mic Element	Stereo Electret Condenser		
Sensitivity	-40dB @ 1kHz (1V/Pa)		
Frequency Response	100-20,000 Hz	100-18,000 Hz	100-20,000 Hz
Low cut	N/A	6dB/Octave @ 200Hz	N/A
Directivity	Uni-directional stereo mic.		
Output Impedance	1.5KΩ @ 1kHz		
Power Source	LR44 Alkaline battery	1.5V DC ("AAA" Battery)	
Battery Life	approx. 150h	approx. 400h	approx. 150h
Max. SPL:	100dB SPL (1kHz @ 1% T.H.D.)		
Signal to Noise	60dB (1kHz @ 1Pa)		
Dimensions	121mm L x 21mm Diameter	177mm L x 18.2mm Diameter	76mm(H) x 52mm(W) x 16.5mm(D)
Weight	2.12oz (60g)	1.83oz (52g)	2.05oz(58g)
Plug Cord Assembly	Coiled cord with 3.5mm mini plug		
Accessories:	Shock-mount holder, Windscreen		

* Due to constant improvements, specifications are subject to change without notice.



	CAM-3 Portable Mixer
Input	3 Mic. (mono x2, stereo x1)
Output	1 stereo mini jack
Input Level	-64dBm
Output Level	-64dBm
Dimensions	88 x 19 x 54 mm 3 1/4" x 1/4" x 2 1/8"
Weight	74g / 3oz

AZDEN corporation

200 Valley Road, Suite 101, Mt. Arlington, NJ 07856, (973)810-3070, FAX (973)810-3076
 e-mail: sales@azdencorp.com, web site: www.azdencorp.com

